



VINYL & WINDSCREEN MESH WARRANTY

MANUFACTURING DEFECTS

Vinyl curtain & windscreens products are warranted completely against manufacturing defects. Such defects include, but are not limited to, uncoated or improperly coated fabric, improper stitching, faulty or improperly placed grommets, defective heat-sealing, or incorrect size. Manufacturing defects would be apparent before use or shortly after cover is put in use and must be delineated to manufacturer at that time. Digital pictures showing defect are required. Manufacturing defect claims for products with extended use may be denied.

Upon verification of defect, manufacturer will either replace cover, repair to customer's satisfaction, or issue full or partial credit.

Manufacturer reserves the right to make the final judgment on the stated options.

Warranty applies under conditions of normal use, but does not apply to problems resulting from unreasonable use, mishandling, negligence or intentional damage.

ULTRA-VIOLET LIGHT BREAKDOWN

Windscreens are warranted against fabric breakdown from the ultra-violet (UV) sunlight.

UV breakdown is evident through brittleness of fabric, greatly reduced tear strength, and, at times, delamination of coating from base fabric.

Upon verification of defect, covers will be repaired, replaced or credit issued for pro-rated value of windscreens. Manufacturer reserves the right to make final judgment on the stated options.

Freight charges for replacement of cover are not included under warranty.

WIND DAMAGE

Damage to windscreens resulting from ties breaking and windscreens pulling free from fence is not

covered under warranty. It is the responsibility of the installer to attach windscreen panels so they will not break away from the fence during windy periods. Grommets are placed at 18" intervals on windscreen panels and it is strongly recommended that a standard wrap (50 lb. tensile strength) tie or cord be attached through every grommet to minimize wind damage.

Additional grommet lines / lacing lips should be added in between top and bottom grommet lines, to better support windscreens in high wind areas.

Additionally, it is recommended that heavy duty tie wrap (120 lb. tensile strength) or cord be used for attachment at every other grommet. Refer to Windscreens Installation Instructions provided with every windscreens order. Additional copies of the Windscreens Installation Instruction can be provided by calling 800-877-6787 or emailing us at info@practicesports.com.

On privacy screen fabric with woven eyelets, ties should be placed at 18" intervals (or closer).

Report windscreens defects in writing to Practice Sports, Inc, PO Box 1463, Bellevue, NE 68005-1463 or info@practicesports.com. Please include proof of purchase.

| WARRANTY IS PRO-RATED | |
|-----------------------|----------|
| PRODUCT | WARRANTY |
| Enviroscreen | 4 years |
| VCP | 4 years |
| VCM | 3 years |
| Aerflo Econo | 2 years |
| Extreme Screen | 7 years |
| Aerflo Tuffy | 5 years |
| Armor Mesh | 5 years |
| Vinyl + Mesh Curtains | 8 years |